

Viga Laminada UPN

Especificaciones Generales

Largo Normal: 6 Mts. Para otros largos consulte

UPN	Altura Total en mm h	Ancho de las alas en mm b	Espesor del alma en mm t	Espesor del alma en mm e	Radio del redondeao del ala en mm R1	Sección A cm2	Peso teórico	Ejes XX e YY			Ix cm4	Wx cm3	ix cm	R
								cm	cm	cm				
80	80	45	6,0	8,0	4,0	11,0	8,64	106	26,5	3,10	19,4	6,36	1,33	8,0
100	100	50	6,0	8,5	4,5	13,5	10,6	206	41,2	3,91	29,3	8,49	1,47	8,5
120	120	55	7,0	9,0	4,5	17,0	13,4	364	60,7	4,62	43,2	11,1	1,59	9,0
140	140	60	7,0	10,0	5,0	20,4	16	605	86,4	5,45	62,7	14,8	1,75	10,0
160	160	65	7,5	10,5	5,5	24,0	18,8	925	116	6,21	85,3	18,3	1,89	10,5
180	180	70	8,0	11,0	5,5	28,0	22	1350	150	6,95	114	22,4	2,02	11,0
200	200	75	8,5	11,5	6,0	32,2	25,3	1910	191	7,70	148	27,0	2,14	11,5
220	220	80	9,0	12,5	6,5	37,4	29,4	2690	245	848,00	197	33,6	2,30	12,5
240	240	85	9,5	13,0	6,5	42,3	33,2	3600	300	9,22	248	39,6	2,42	13,0
260	260	90	10,0	14,0	7,0	48,3	37,9	4820	317	9,99	317	74,7	2,56	14,0
280	280	95	10,0	15,0	7,5	53,3	41,8	6280	448	10,90	399	57,2	2,74	15,0
300	300	100	10,0	16,0	8,0	58,8	46,2	8030	535	11,70	495	67,8	2,90	16,0
320	320	100	14,0	17,5	8,8	75,8	59,5	10870	679	12,10	597	80,6	2,81	17,5
350	350	100	14,0	16,0	8,0	77,3	60,6	12840	734	12,90	570	75,0	2,72	16,0
380	380	102	13,5	16,0	8,0	80,4	63,1	15760	829	14,00	615	78,7	2,77	16,0
400	400	110	14,0	18,0	9,0	91,5	71,8	20350	1020	14,90	846	102,0	3,04	18,0

